

538,593

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
**WO 2004/054099 A1**

(51) International Patent Classification<sup>7</sup>:  
// 5/02, 5/16

**H03G 5/00**

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/DK2002/000831

(22) International Filing Date: 9 December 2002 (09.12.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): CHRISTENSEN, Knud, Bank [DK/DK]; Skovvej 2, DK-8550 Ryomgård (DK). PEDERSEN, Kim, Rishøj [DK/DK]; Skæring Sandager 54, DK-8250 Egå (DK).

(74) Agent: PATENTGRUPPEN ApS; Arosgården, Åboulevarden 31, DK-8000 Aarhus C (DK).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/054099 A1

(54) Title: A FULLY PARAMETRIC EQUALIZER

(57) Abstract: The invention relates to a parametric equalizer comprising filtering means (FM), user interface means (UIM), audio signal input means and audio signal output means, said filtering means comprising at least one filter block (FIB) said user interface means (UIM) facilitating adjustment of corner frequency (fc), Shape (Q) and gain (G), said user interface means (UIM) comprising a further adjustment parameter (SYM), said user interface means being mapped by means of coefficient adjustment algorithms (CAD) into filter coefficient settings (FCP) of the at least one filter block (FIB), which when established reflects the adjustment of the user interface means (UIM) said further adjustment parameter (SYM) providing a filter coefficient setting (FCS) comprising a combined adjustment of at least one zero frequency, pole frequency, zero Q and pole Q of at least one filter block.